§421.83

40 CFR Ch. I (7-1-06 Edition)

§ 421.83 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable:

(a) Subpart H—Zinc Reduction Furnace Wet Air Pollution Control.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of zinc reduced	
Cadmium Copper Lead Zinc	.334 2.135 .467 1.702	.134 1.018 .217 .701

(b) Subpart H—Preleach of Zinc Concentrates.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of concentrate leached	
Cadmium	.180 1.153	.072 .550
Lead	.252	.117
Zinc	.919	.378

(c) Subpart H—Leaching Wet Air Pollution Control.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of zinc proc- essed through leaching	
Cadmium	.000	.000
LeadZinc	.000	.000

(d) Subpart H—Electrolyte Bleed Wastewater.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		ds per million cathode zinc
Cadmium	.086 .553	.035 .264
Lead	.121	.056
Zinc	.441	.182

(e) Subpart H—Cathode and Anode Wash Wastewater.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		ds per million cathode zinc
Cadmium	.150 .961 .210	.060 .458 .098 .315

(f) Subpart H—Casting Wet Air Pollution Control.

BAT EFFLUENT LIMITATIONS

Maximum for any 1 day	Maximum for monthly average
mg/kg (pounds per million pounds) of zinc cast	
.051	.021
.329	.157
.072	.033
.262	.108
	mg/kg (pounds) o .051 .329 .072

(g) Subpart H—Casting Contact Cooling.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of zinc cast	
Cadmium	.036 .232 .051 .185	.014 .110 .024 .076

(h) Subpart H—Cadmium Plant Wastewater.

Environmental Protection Agency

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of cadmium pro- duced	
Cadmium	1.234	.494
Copper	7.899	3.765
Lead	1.728	.802
Zinc	6.295	2.592

§421.84 Standards of performance for new sources.

Any new source subject to this subpart shall achieve the following new source performance standards:

(a) Subpart H—Zinc Reduction Furnace Wet Air Pollution Control.

NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of zinc reduced	
Cadmium	.334	.134
Copper	2.135	1.018
Lead	.467	.217
Zinc	1.702	.701
Total suspended solids	25.020	20.020
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(b) Subpart H—Preleach of Zinc Concentrates.

NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millior pounds) of concentrate leached	
Cadmium	.180	.072
Copper	1.153	.550
Lead	.252	.117
Zinc	.919	.378
Total suspended solids	13.520	10.810
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(c) Subpart H—Leaching Wet Air Pollution Control.

NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millior pounds) of zinc proc essed through leaching	
Cadmium	.000	.000
Copper	.000	.000
Lead	.000	.000
Zinc	.000	.000
Total suspended solids	.000	.000
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(d) Subpart H—Electrolyte Bleed Wastewater.

NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millio pounds) of cathode zin produced	
Cadmium Copper Lead Zinc Total suspended solids pH	.086 .553 .121 .441 6.480 (¹)	.035 .264 .056 .182 5.184 (¹)

 $^{^{\}mbox{\tiny 1}}\mbox{Within the range of 7.5 to 10.0 at all times.}$

(e) Subpart H—Cathode and Anode Wash Wastewater.

NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of cathode zinc produced	
Cadmium Copper Lead Zinc Total suspended solids pH	.150 .961 .210 .766 11.270 (¹)	.060 .458 .098 .315 9.012

¹ Within the range of 7.5 to 10.0 at all times.

(f) Subpart H—Casting Wet Air Pollution Control.

NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of zinc cast	
Cadmium	.051 .329 .072	.021 .157 .033